Material safety data sheet for chemical products (MSDS)

1. PRODUCT AND COMPANY IDENTIFICATION

 Product name : Nickel-Metal Hydride Battery : Cyclindical and Rectangular (Appendix A) Supplier's Name : MAHA ENERGY CORP. Supplier's Address : 14311 Chambers Rd., Tustin, CA 92780, U.S.A. Telephone number : 1-800-376-9992 Manufacturer's Name : MAHA ENERGY CORP. Manufacturer's Address : 14311 Chambers Rd., Tustin, CA92780, U.S.A. Telephone number : 1-800-376-9992 				
 Supplier's Address Supplier's Address 14311 Chambers Rd., Tustin, CA 92780, U.S.A. Telephone number 1-800-376-9992 Manufacturer's Name MAHA ENERGY CORP. 14311 Chambers Rd., Tustin, CA92780, U.S.A. 	 Product name : Nickel-Metal I 	Hydride Battery : Cyclindical and Rectangular (Appendix A)		
Tustin, CA 92780, U.S.A.• Telephone number: 1-800-376-9992• Manufacturer's Name: MAHA ENERGY CORP.• Manufacturer's Address: 14311 Chambers Rd., Tustin, CA92780, U.S.A.	 Supplier's Name 	: MAHA ENERGY CORP.		
 Telephone number Manufacturer's Name MAHA ENERGY CORP. Manufacturer's Address 14311 Chambers Rd., Tustin, CA92780, U.S.A. 	 Supplier's Address 	: 14311 Chambers Rd.,		
 Manufacturer's Name : MAHA ENERGY CORP. Manufacturer's Address : 14311 Chambers Rd., Tustin, CA92780, U.S.A. 		Tustin, CA 92780, U.S.A.		
Manufacturer's Address : 14311 Chambers Rd., Tustin, CA92780, U.S.A.	 Telephone number 	: 1-800-376-9992		
	 Manufacturer's Address 	: 14311 Chambers Rd., Tustin, CA92780, U.S.A.		

2.HAZARDS IDENTIFICATION

· Most important hazard and effects

For the battery cell, chemical materials are stored in a hermetically sealed metal case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials' leakage.

However, if exposed to a fire, added mechanical shocks, decomposed, added electric stress by misuse, the gas release vent will be operated. The battery cell case will be breached at the extreme. Hazardous materials may be released.

Moreover, if heated strongly by the surrounding fire, acrid or harmful fume may be emitted.

Human health effects:

Inhalation: The electrolyte inhalation affects the respiratory tract membrane and the lungs. Fume may cause a cough, chest pain and dyspnea. Bronchitis and pneumonia may occur. Possibly could be carcinogen.

Skin contact: The electrolyte skin contact affects the skin seriously and may cause dermatitis.

- Eye contact: The electrolyte leaked from the battery cell is strong alkali. When it goes into an eye, the cornea may be affected and it may lead to blindness.
- Ingestion: The electrolyte ingestion irritates the mouth and the throat seriously results in vomiting, nausea, hematemesis, stomach pains and diarrhea.

Environmental effects:

Since a battery cell remains in the environment, do not throw out it into the environment.

Specific hazards :

As previously described.

3.COMPOSITION / INFORMATION ON INGREDIENTS

- Substance or preparation : Preparation
- · Information about the chemical nature of product :

Common chemical name / General name	CAS number	Concentration / Concentration range	Classification and hazard labeling
Hydrogen Absorbing Alloy	7440-02-0(Ni)	Concentration range	specific hazard
	7440-48-4(Co)	20-40%	specific flazard
	7439-96-5(Mn)	20 40 /0	
	7429-90-5(AI)		
Nickel-Cobalt-Zinc oxide	7440-02-0(Ni)	15-25%	acute toxicity
	7440-48-4(Co)		specific hazard
	7440-66-6(Zn)		·
Nickel	7440-02-0	5-15%	specific hazard
Iron	7439-89-6	20-40%	
Carbon Black	1333-86-4	0-1%	specific hazard
Potassium Hydroxide	1310-58-3		acute toxicity
Sodium Hydroxide	1310-73-2	0-15%	corrosivity
Lithium Hydroxide	1310-65-2	1	irritant property

4.FIRST-AID MEASURES

Internal cell materials of an opened battery cell

Inhalation :

Cover the victim in a blanket, move to the place of fresh air and keep quiet. Seek medical attention immediately. When dyspnea (breathing difficulty) or asphyxia (breath-hold), give artificial respiration immediately.

Skin contact :

Remove contaminated clothes and shoes immediately. Wash the adherence or contact region with soap and plenty of water. Seek medical attention immediately.

· Eye contact :

Immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention immediately.

A battery cell and internal cell materials of an opened battery cell

Ingestion :

Do not induce vomiting. Seek medical attention immediately.

5.FIRE-FIGHTING MEASURE

Although a battery cell is not flammability, in case of fire, move it to the safe place quickly.

The following measures are taken when it cannot be moved.

- Suitable extinguishing media: Dry sand, chemical powder fire extinguishing medium.
- · Specific hazards: Acrid or harmful fume is emitted during fire.
- Special protective equipment for firefighters : Protective equipment written in Section 8.

6.ACCIDENTAL RELEASE MEASURES

Internal cell materials, such as electrolyte leaked from battery cell, are carefully dealt with according to the followings.

Personal precautions :

Forbid unauthorized person to enter. Remove leaked materials with protective equipment written in Section 8.

- · Environmental precautions: Do not throw out into the environment.
- · Method of recovery and neutralization :

Dilute the leaked electrolyte with water and neutralize with diluted sulfuric acid. The leaked solid is moved to a container. The leaked place is fully flushed with water.

7.HANDLING AND STORAGE

Handling

Technical measures

Prevention of user exposure: Not necessary under normal use.

Prevention of fire and explosion: Not necessary under normal use.

Precaution for safe handling: Do not damage or remove the external tube.

Specific safe handling advice: Never throw out cells in a fire or expose to high temperatures. Do not soak cells in water and seawater. Do not expose to strong oxidizers. Do not give a strong mechanical shock or throw down. Never disassemble, modify or deform. Do not connect the positive terminal to the negative terminal with electrically conductive material. In the case of charging, use only dedicated charger or charge according to the conditions specified by Quanstek.

Storage

Technical measures

Storage conditions (suitable to be avoided): Avoid direct sunlight, high temperature, high humidity. Store in cool place (temperature: -20 ~ 30 degree C, humidity: from 40 to 80%).

Incompatible products: Conductive materials, water, seawater, strong oxidizers and strong acids Packing material (recommended, not suitable): Insulative and tear-proof materials are recommended.

8.EXPOSOURE CONTROLS / PERSONAL PROTECTION

• Engineering measures :

No engineering measure is necessary during normal use. In case of internal cell materials' leakage, the information below will be useful.

Control parameters

Common chemical name / General name	ACGIH(2011)		
	TLV-TWA	BEI	
Nickel, Nickel Compounds	(As Ni) Metal : 1.5mg/m ³ Soluble compounds : 0.1mg/m ³ Insoluble compounds : 0.2mg/m ³	-	
Cobalt Compounds	(As Co) 0.02mg/m ³	In urine : 15 micro g/l In blood : 1 micro g/l	
Manganese Compounds	(As Mn) 0.2mg/m ³	-	
Aluminum Compounds	(As Al) 1mg/m ³ (Flammable powder)	-	
Zinc oxide	2mg/m ³	-	
Carbon Black	3mg/m ³	-	
Potassium Hydroxide	-	-	
Sodium Hydroxide	-	-	
Lithium Hydroxide	-	-	

ACGIH: American Conference of Governmental Industrial Hygienists, Inc. TLV-TWA: Threshold Limit Value-time weighted average concentration BEI: Biological Exposure Indices

· Personal protective equipment

Respiratory protection: Protective mask Hand protection: Protective gloves Eye protection: Protective glasses designed to protect against liquid splashes Skin and body protection: Working clothes with long sleeve and long trousers

9.PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state: Solid

Form: Cylindrical and Prismatic Color: Metallic color (without tube/label) Odour: No odour

• pH : NA

• Specific temperatures/temperature ranges at which changes in physical state occur : There is no useful information for the product as a mixture.

- · Flash point : NA
- Explosion properties : NA
- Density : around 1.5 ~ 6.0g/cm³
- · Solubility ,with indication of the solvent(s) : Insoluble in water

10.STABILITY AND REACTIVITY

- Stability : Stable under normal use
- Hazardous reactions occurring under specific conditions

By misuse of a battery cell or the like, oxygen or hydrogen accumulates in the cell and the internal pressure rises. These gases may be emitted through the gas release vent. When fire is near, these gases may take fire.

When a battery cell is heated strongly by the surrounding fire, acrid or harmful fume may be emitted.

- Conditions to avoid : Direct sunlight, high temperature and high humidity
- Materials to avoid : Conductive materials, water, seawater, strong oxidizers and strong acids
- Hazardous decomposition products: Acrid or harmful fume is emitted during fire.

11.TOXICOLOGICAL INFORMATION

There is no data available on the product itself. The information of the internal cell materials is as follows.

Nickel, Nickel Compou	Inds
 Acute toxicity: 	
oral	GHS: out of Category.
skin	Unknown.
inhalation (gas) inhalation (steam)	GHS: exempt from a classification.
inhalation (steam)	Unknown.
. ,	
 Skin corrosivity : Serious damage and 	Unknown. irritant property for eyes: Unknown.
 Respiratory or skin se 	
	ry sensitization: GHS: Category 1
	he allergy, asthma or breathing difficulties might be caused when inhaling.
Skin sens	
TI	ne allergic skin reaction might be caused.
 Germline mutagenicity 	
	not possible to classify it due to data deficiency.
 Carcinogenicity : 	
GHS: Category 2	
	5 – Not suspected as a human carcinogen
	bluble compounds) A4 – Not classified as a human carcinogen obviously e compounds) A1 – Confirmed human carcinogen
	occupational carcinogen
	anticipated to be human carcinogen
	pup 2B Possibly carcinogenic to human
	ds) Group 1 carcinogenic to human
 Reproduction Toxicity 	:
GHS: It is	not possible to classify it due to data deficiency.
	Systemic toxicity (single exposure):
	egory 1(respiratory organ and kidney).
	der of the respiratory organ and the kidney is caused.
	Systemic toxicity (repeated exposure):
	egory 1(respiratory organ). der of the respiratory organ is caused by long-term or repeated exposure.
	der of the respiratory organ is caused by long-term of repeated exposure.
Cobalt Compounds	
Acute toxicity:	
oral	GHS: out of Category.
skin	Unknown.
inhalation (gas)	GHS: exempt from a classification.
inhalation (steam)	Unknown.
inhalation (mist)	GHS: It is not possible to classify it due to data deficiency.
 Skin corrosivity : 	Unknown.
 Serious damage and 	irritant property for eyes: Unknown.
 Respiratory or skin se 	
	ry sensitization: GHS: Category 1
	ne allergy, asthma or breathing difficulties might be caused when inhaling.
Skin sens	5,
	ne allergic skin reaction might be caused.
 Germline mutagenicity Carcinogenicity : 	y: Unknown.
GHS: Category 2	
	firmed animal carcinogen but relevance to human carcinogen is unknown.
	Possibly carcinogenic to human.
The cancer might	

- Reproduction Toxicity :
 - GHS: Category 2.
 - The adverse effect on reproductive competence or the fetus might occur.
- Certain target organ/ Systemic toxicity (single exposure):
 - GHS: Category 3(respiratory tract irritating properties).
 - The respiratory organ might be stimulated.
- Certain target organ/ Systemic toxicity (repeated exposure):
 - GHS: Category 1(respiratory organ).
 - The disorder of the respiratory organ is caused by long-term or repeated exposure.

Manganese compounds

- Acute toxicity: oral GHS: out of Category. skin Unknown. inhalation (gas) GHS: exempt from a classification. inhalation (steam, mist) Unknown.
- Skin corrosivity : GHS: Category 3. Slight skin stimulation.
- Serious damage and irritant property for eyes: GHS: Category 2B. eye stimulation.
- Respiratory or skin sensitization:

Respiratory sensitization: Unknown.

Skin sensitization: Unknown.

- Germline mutagenicity : GHS: It is not possible to classify.
- Carcinogenicity : GHS: out of Category.
- Reproduction Toxicity : GHS: Category 1B.
- The adverse effect on reproductive competence or the fetus might occur.
- Certain target organ/ Systemic toxicity (single exposure): GHS: Category 1(respiratory organ).

The disorder of the respiratory organ is caused.

Certain target organ/ Systemic toxicity (repeated exposure):

GHS: Category 1(respiratory organ, nerve).

The disorder of the respiratory organ and nerve system is caused by long-term or repeated inhalation exposure.

Aluminum Compounds

- Acute toxicity:
- oral, skin, inhalation(steam, dust) Unknown.
- Skin corrosivity : Unknown.
- Serious damage and irritant property for eyes: Unknown.
- · Respiratory or skin sensitization:
 - Respiratory sensitization: Unknown.
 - Skin sensitization: Unknown.
- Germline mutagenicity : Unknown. Unknown.
- · Carcinogenicity :
- Reproduction Toxicity : Unknown.
- Certain target organ/ Systemic toxicity (single exposure):
- Certain target organ/ Systemic toxicity (repeated exposure):

GHS: Category 1 and 2.

The disorder of the pulmonary is caused by long-term or repeated inhalation exposure.(Category 1) The disorder of the nerve system by long-term or repeated oral exposure might be caused. (Category 2)

Unknown.

Zinc oxide

- Acute toxicity: oral rat LD₅₀ > 5000mg/kg inhalation (dust, mist) rat $LC_{50} > 5.7$ mg/l The harmful might be caused when inhaling.
- Skin corrosivity : GHS: out of Category.
- Serious damage and irritant property for eyes: GHS: out of Category

- Respiratory or skin sensitization:
 - Respiratory sensitization: Unknown.
 - Skin sensitization: GHS: out of Category.
- Germline mutagenicity : Unknown.
- Carcinogenicity : GHS: out of Category.
- Reproduction Toxicity : GHS: out of Category.
- Certain target organ/ Systemic toxicity (single exposure):
 - GHS: Category 1.

The disorder of the whole body

- Certain target organ/ Systemic toxicity (repeated exposure):
 - GHS: Category 1.
 - The disorder of the pulmonary is caused by long-term or repeated inhalation exposure.

Carbon Black

Acute toxicity:

- oral rat LD₅₀ >15400 mg/kg skin Unknown. inhalation (dust) Unknown.
- Skin corrosivity : Unknown.
- Serious damage and irritant property for eyes: Unknown.
- Respiratory or skin sensitization:
 - Respiratory sensitization:Unknown.Skin sensitization:Unknown.
- Germline mutagenicity : Unknown.
- · Carcinogenicity :
 - GHS: Category 2

ACGIH: A3 –Confirmed animal carcinogen but relevance to human carcinogen is unknown. IARC: Group 2B Possibly carcinogenic to human.

- The cancer might be caused.
- Reproduction Toxicity : Unknown.
- Certain target organ/ Systemic toxicity (single exposure): Unknown.
- Certain target organ/ Systemic toxicity (repeated exposure):
 - GHS: Category 1

The disorder of the pulmonary is caused by long-term or repeated inhalation exposure.

Potassium Hydroxide

- Acute toxicity: oral
 Skin
 inhalation (steam)
 inhalation (dust)
 GHS: It is not possible to classify.
 GHS: It is not possible to classify.
- Skin corrosivity : GHS: Category 1B.
 - Serious chemical wound of the skin and damage of eyes is caused.
- Serious damage and irritant property for eyes: GHS: Category 1.
- Respiratory or skin sensitization:
 - Respiratory sensitization: GHS: It is not possible to classify.
 - Skin sensitization: GHS: out of Category.
- Germline mutagenicity : GHS: out of Category.
- Carcinogenicity : GHS: It is not possible to classify.
- Reproduction Toxicity : GHS: It is not possible to classify.
- Certain target organ/ Systemic toxicity (single exposure):
 - GHS: Category 1.
 - The disorder of the respiratory system is caused.
- Certain target organ/ Systemic toxicity (repeated exposure)
 - GHS: It is not possible to classify.

Sodium Hydroxide

 Acute toxicity: 	
oral	GHS: It is not possible to classify.
skin	GHS: It is not possible to classify.
inhalation (gas)	GHS: out of Category.
inhalation (steam)	Unknown.
inhalation (dust)	Unknown.
Skin correctivity :	CHS: Category 1

 Skin corrosivity : GHS: Category 1.

Serious chemical wound of the skin and damage of eyes is caused.

- Serious damage and irritant property for eyes: GHS: Category 1. Serious damage of eyes is caused.
- · Respiratory or skin sensitization: Respiratory sensitization: GHS: It is not possible to classify. Skin sensitization: GHS: out of Category.
- Germline mutagenicity : GHS: out of Category
- Carcinogenicity: GHS: It is not possible to classify.
- Reproduction Toxicity : GHS: It is not possible to classify.
- Certain target organ/ Systemic toxicity (single exposure):
 - GHS: Category 1(respiratory system).
 - The disorder of the respiratory organ is caused.
- Certain target organ/ Systemic toxicity (repeated exposure): GHS: It is not possible to classify.

Lithium Hydroxide

 Acute toxicity: 		
oral	GHS: Category 3.	Harmful if swallowed.
skin	Unknown.	
inhalation (steam)	Unknown.	
inhalation (dust)	GHS: Category 3.	Harmful if inhaled.
Skin corrosivity :	GHS: Category 1.	
2	Serious chemical w	yound of the skin and damage of eves is caused

- Serious chemical wound of the skin and damage of eyes is caused. GHS: Category 1.
- Serious damage and irritant property for eyes:
- Respiratory or skin sensitization: Respiratory sensitization: GHS: It is not possible to classify.
 - Skin sensitization: GHS: It is not possible to classify.
- Germline mutagenicity : Unknown.
- Carcinogenicity : Unknown.
- Reproduction Toxicity : Unknown.
- Certain target organ/ Systemic toxicity (single exposure):
 - GHS: Category 1.
 - The disorder of the respiratory system is caused by inhalation exposure.

Certain target organ/ Systemic toxicity (repeated exposure):

GHS: Category 1&2.

The disorder of the respiratory system is caused by long-term or repeated inhalation exposure. The disorder of the liver and the hematopoietic system by long-term or repeated oral exposure might be caused.

12.ECOLOGICAL INFORMATION

· Persistence/degradability :

Since a battery cell and the internal materials remain in the environment, do not bury or throw out into the environment.

13.DISPOSAL CONSIDERATIONS

· Recommended methods for safe and environmentally preferred disposal :

Product (waste from residues)

Do not throw out a used battery cell. Recycle it through the recycling company.

Contaminated packaging

Neither a container nor packing is contaminated during normal use. When internal materials leaked from a battery cell contaminates them, dispose them as industrial wastes subject to special control.

14.TRANSPORT INFORMATION

This battery does not require the following items.

- TECHNICAL INSTRUCTIONS FOR THE SAFE TRANSPORT OF DANGEROUS GOODS BY AIR(ICAO)
- IATA Dangerous Goods Regulations(IATA)
- · code of federal regulations (U.S.DOT)

This battery requires the following items.

• INTERNATIONAL MARITIME DANGEROUS GOODS CODE(IMO)

From the 1st January 2012, Nickel-Metal Hydride Batteries is classed as Dangerous Goods, Class 9 in accordance with United Nations Recommendations on the Transport of Dangerous Goods and will have the following UN Number:

UN No.	Proper Shipping Name	Class or	Packing	Special
		division	group	provisions
3496	BATTERIES, NICKEL-METAL HYDRIDE	9	-	117
				963

Instructions and contents of Special Provisions (117 and 963) for this UN number include:

- · Specifying it is only regulated when transported by sea,
- Ni-MH button cells are not subject to the provisions of this code.
- Ni-MH cells or batteries packed with or contained in equipment are not subject to the provisions of this code.
- All other Ni-MH cells or batteries shall be securely packed and protected from short circuit. They are not subject to other provisions of this code provided they are loaded in a cargo transport unit in a total quantity of less than 100 Kg gross mass.

When loaded in a cargo transport unit in a total quantity of 100 Kg gross mass or more, only subject to:

- Provided dangerous goods transportation information by a) Consignor and b) Shipper.
- Stowage and segregation provisions: as prescribed in Chapter 3 of IMDG Code: "away from" sources of heat as minimum horizontal separation of 3 metres.

Prior to transportation, confirmation that there is no leakage and no spillage from a container is necessary. Cargo must be handle without falling, dropping or breakage. Care must be taken to prevent the collapse of cargo piles or saturation by rain. Containers must be handled carefully. Packaging is constructed to prevent short-circuiting and/or electric shock. The product is handled as Non-Dangerous Goods by based on IATA(A123) for air shipment.

15.REGULATORY INFORMATION

 Regulations specifically applicable to the product : Wastes Management and Public Cleaning Law (Japan) Law for Promotion Effective Utilization of Resources (Japan) Commission Directive 2006/66/EU (EU) **16.OTHER INFORMATION**

- The information contained in this Safety data sheet is based on the present state of knowledge and current legislation.
- This safety data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Reference

Chemical substances information: Japan Advanced Information center of Safety and Health International Chemical Safety Cards (ICSCs):

International Occupational Safety and Health Information Center (CIS) 2011 TLVs and BEIs : American Conference of Governmental Industrial Hygienists (ACGIH) NIOSH CARCINOGEN LIST: National Institute for Occupational Safety and Health (NIOSH) The Ninth Report on Carcinogen: National Toxicology Program (NTP) IARC Monographs Program on the Evaluation of Carcinogenic Risks to Humans: International Agency for Research on Cancer (IARC) Globally Harmonized System of Classification and Labelling of Chemicals(GHS) National Institute of Technology and Evaluation(NITE)

> First edition Dec.1, 2003 Latest edition May.02, 2023 Prepared and approved by Maha Energy Corp.

Establishment / Revision: May.02.2023

Appendix A

PRODUCT LIST :